NSN 5305-01-084-6065

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-084-6065 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.340 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: Between 25.0 rockwell c and 38.0 rockwell c **Screw Material:** Steel **Screw Material Specification:** Sae j28 grade 120m assn standard single material response **Screw Surface Treatment:** Cadmium or zinc **Screw Surface Treatment Specification:** Bw-101b-p fscm 06853 mfr ref 1st treatment response or bw-101b-p fscm 06853 mfr ref 2nd treatment response **Special Features:** Furnished with one removable helical spring lockwasher **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-084-6065

Machine Screw - Page 2 of 2



Fiig:

A500d0