# NSN 5305-01-084-6067

Tapping Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-084-6067

#### Fastener Length:

Between 0.470 inches and 0.500 inches

#### Head Style:

Hexagon extended washer

#### Head Height:

Between 0.202 inches and 0.240 inches

#### Width Between Flats:

Between 0.367 inches and 0.375 inches

#### **Extended Washer Diameter:**

Between 0.480 inches and 0.520 inches

#### Extended Washer Thickness:

Between 0.030 inches and 0.050 inches

Internal Drive Style:

W/o internal drive

**Features Provided:** 

Casehardened

#### Min. Tensile Strength (psi):

150000 pounds per square inch

#### Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

#### Nonmachine Thread Style:

Dog type (type b or c)

#### Nonmachine Thread Diameter:

0.250 inches

Material:

Steel comp 4037

#### **Material Specification:**

66 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification single treatment response or mil-c-81562 type 2 class 2 military specification single treatment

response

#### **Specification Or Standard:**

B type or c type

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

### Fiig:

A003b0

# NSN 5305-01-084-6067

Tapping Screw - Page 2 of 2

### Mil-std (military Standard):

Mil-c-81562 spec.

