

View Online at <https://aerobasegroup.com/nsn/5305-01-084-8560>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.625 inches

**Fastener Length:**

0.625 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.176 inches and 0.183 inches

**Head Height:**

Between 0.108 inches and 0.112 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.112 inches

**Width Across Flats:**

0.094 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

155000 pounds per square inch

**Special Features:**

Critical item hydrogen embrittlement relief required

**Material:**

Steel

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

Qq-z-325, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0