NSN 5305-01-084-8561

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-084-8561

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.500 inches |
| Fastener Length: |
| 4.500 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.735 inches and 0.750 inches |
| Head Height: |
| Between 0.492 inches and 0.500 inches |
| Locking Feature: |
| Patch threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.500 inches |
| Width Across Flats: |
| 0.375 inches |
| Thready Qty Per Inch (tpi): |
| 13 |
| Min. Tensile Strength (psi): |
| 170000 pounds per square inch |
| Hardness Rating: |
| 38.0 rockwell c and 45.0 rockwell c |
| Minimum Yield Strength: |
| 150000 pounds per square inch |
| Special Features: |
| Ritical item hydrogen embrittlemet relief required |
| Material: |
| Steel |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Zinc |
| Surface Treatment Specification: |
| Qq-z-325, type 2, cl 3 federal specification single treatment response |
| Thread Series Designator: |

Unc

NSN 5305-01-084-8561

Socket Head Cap Screw - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| CI | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0