## NSN 5305-01-084-8564

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-084-8564

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
2.500 inches
Fastener Length:
3.000 inches
Head Style:
Fillister
Head Diameter:
Between 1.479 inches and 1.500 inches
Head Height:
Between 0.988 inches and 1.000 inches
Locking Feature:
Patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
1.000 inches
Width Across Flats:
0.750 inches
Thready Qty Per Inch (tpi):
8
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Special Features:
Critical item hydrogen embrittlement relief required
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Zinc
Surface Treatment Specification:
Qq-z-325, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unc

## NSN 5305-01-084-8564

Socket Head Cap Screw - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0