NSN 5305-01-084-8568

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-084-8568

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.380 inches |
| Fastener Length: |
| 4.468 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.530 inches and 0.562 inches |
| Head Height: |
| Between 0.368 inches and 0.375 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.375 inches |
| Width Across Flats: |
| 0.312 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Material: |
| Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |