NSN 5305-01-085-1012

Demilitarization:

No Fiig: A500d0



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-085-1012 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.730 inches and 1.770 inches **Fastener Length:** Between 1.800 inches and 1.850 inches **Head Style:** Fillister **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 304 or steel comp 304l **Screw Material Specification:** Qq-s-763 federal specification 1st material response and 66 federal specification 1st material response **Special Features:** Passivated per federal specifica tion qq-p-35; recess conforms to ms9006driver size number 1; magnetic permeab ility: 2.0 ma (air-1.0) for a field strength of h-2000 oersteds using a magnetic indicator per mil-i-17214; dimensional limits and surface texturedesignations apply after passivation **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**