Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-085-3229

| 3a Thread Direction: Right-hand Thread Length: 0.750 inches Fastener Length: Between 0.845 inches and 0.875 inches Head Style: Flat chamfer Head Dimeter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches With Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium and chromate Surface Treatment Specification Gurp-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| Thread Direction:Right-handThread Length:0.750 inchesFastener Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMininum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateChread Series Designator:UrrcSpecification Stale StrengtoriesAndres Stales:Stafes Treatment Specification single treatment responseThread Series Designator:UrrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Thread Class: |
| Right-handRight-handThread Length:0.750 inchesFastener Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateCadrium and chromateCadrium and chromateStread Streis Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | |
| Tread Length:0.750 inchesFastener Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inches0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):18000 pounds per square inchHardness Rating:0300 pounds per square inchMinimum Yield Strength:15500 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateCadmium and chromateCadmium and chromateSurface Treatment Specification:Quep-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UrrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | |
| 0.750 inchesFastener Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:35.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseThread Stries Designator:UnrcSurface Treatment Specification single treatment responseFiread Stries Designator:UnrcSurface Treatment Specification single treatment responseFiread Stries Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | - |
| Fasterer Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment:Qap-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Thread Length: |
| Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):18000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment:Qu-p-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | 0.750 inches |
| Head Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Fastener Length: |
| Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Qap-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Between 0.845 inches and 0.875 inches |
| Head Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Qap-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Head Style: |
| Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Flat chamfer |
| Head Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateQr-p-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Head Diameter: |
| Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qa-p-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Between 0.218 inches and 0.226 inches |
| Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Hinimum Yield Strength: 155000 pounds per square inch Material: Steel Strel Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Head Height: |
| HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment SpecificationQa-p-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Between 0.134 inches and 0.138 inches |
| Thread Diameter:0.138 inchesWidth Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateGurp-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardKaleN/a | Internal Drive Style: |
| 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qap-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Hexagon |
| Width Across Flats:Between 0.1094 inches and 0.1111 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Thread Diameter: |
| Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | 0.138 inches |
| Thready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Width Across Flats: |
| 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Between 0.1094 inches and 0.1111 inches |
| Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Thready Qty Per Inch (tpi): |
| 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | 32 |
| Hardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Min. Tensile Strength (psi): |
| 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | 180000 pounds per square inch |
| Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Hardness Rating: |
| 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | 38.0 rockwell c and 45.0 rockwell c |
| Material:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment responseThread Series Designator:UnrcSpecification Data:80205-nas1352 professional/industrial association standardShelf Life:N/a | Minimum Yield Strength: |
| Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | 155000 pounds per square inch |
| Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Material: |
| Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Steel |
| Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Surface Treatment: |
| Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Cadmium and chromate |
| Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Surface Treatment Specification: |
| Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Qq-p-416 type 2 cl 2 federal specification single treatment response |
| Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Thread Series Designator: |
| 80205-nas1352 professional/industrial association standard Shelf Life: N/a | Unrc |
| Shelf Life: N/a | Specification Data: |
| N/a | 80205-nas1352 professional/industrial association standard |
| | Shelf Life: |
| | N/a |
| Unit Of Measure: | Unit Of Measure: |
| | |

NSN 5305-01-085-3229

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

