

View Online at <https://aerobasegroup.com/nsn/5305-01-085-7015>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.365 inches and 0.375 inches

**Fastener Length:**

Between 1.995 inches and 2.005 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.609 inches and 0.641 inches

**Head Height:**

Between 0.672 inches and 0.703 inches

**Point Length:**

0.250 inches

**Point Diameter:**

Between 0.214 inches and 0.230 inches

**First Diameter From Head:**

Between 0.225 inches and 0.235 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 1.365 inches and 1.385 inches

**Point Style:**

Cone

**Internal Drive Style:**

Slot

**End Application:**

1420-01-157-6131

**Thread Diameter:**

0.312 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

18

**Externally Relieved Body Diameter Quantity:**

1

**Point Chamfer Angle:**

Between 85.0 degrees and 95.0 degrees

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-764, class 7, type a federal specification single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Thread Series Designator:**

Unc

**Specification Data:**

53711-5165238 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.