NSN 5305-01-085-7015

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-085-7015 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.365 inches and 0.375 inches **Fastener Length:** Between 1.995 inches and 2.005 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.609 inches and 0.641 inches **Head Height:** Between 0.672 inches and 0.703 inches Point Length: 0.250 inches **Point Diameter:** Between 0.214 inches and 0.230 inches **First Diameter From Head:** Between 0.225 inches and 0.235 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.365 inches and 1.385 inches **Point Style:** Cone **Internal Drive Style:** Slot **End Application:** 1420-01-157-6131 **Thread Diameter:** 0.312 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 18 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 85.0 degrees and 95.0 degrees Material:

Steel comp 303

Material Specification:

Qq-s-764, class 7, type a federal specification single material response

NSN 5305-01-085-7015

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924 military specification single treatment response
Thread Series Designator:
Unc
Specification Data:
53711-5165238 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-13924 spec.