

View Online at <https://aerobasegroup.com/nsn/5305-01-086-1076>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.473 inches and 0.540 inches

Fastener Length:

Between 1.078 inches and 1.125 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.120 inches and 0.136 inches

Width Between Flats:

Between 0.244 inches and 0.250 inches

Extended Washer Diameter:

Between 0.358 inches and 0.380 inches

Extended Washer Thickness:

Between 0.019 inches and 0.031 inches

Washer Quantity:

1

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

44.0 rockwell c primary washer and 48.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.370 inches and 0.380 inches

Primary Washer Style:

Finishing

Primary Washer Material Thickness:

0.025 inches

Material:

Steel comp 1030 primary washer

Material Specification:

Sae assn standard 2nd material response primary washer

Surface Treatment:

Cadmium primary washer

Surface Treatment Specification:

G-4341-m code 15 fsc-16764 mfr ref 1st treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0