

View Online at <https://aerobasegroup.com/nsn/5305-01-086-1076>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.473 inches and 0.540 inches

**Fastener Length:**

Between 1.078 inches and 1.125 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

Between 0.120 inches and 0.136 inches

**Width Between Flats:**

Between 0.244 inches and 0.250 inches

**Extended Washer Diameter:**

Between 0.358 inches and 0.380 inches

**Extended Washer Thickness:**

Between 0.019 inches and 0.031 inches

**Washer Quantity:**

1

**Internal Drive Style:**

W/o internal drive

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

44.0 rockwell c primary washer and 48.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.370 inches and 0.380 inches

**Primary Washer Style:**

Finishing

**Primary Washer Material Thickness:**

0.025 inches

**Material:**

Steel comp 1030 primary washer

**Material Specification:**

Sae assn standard 2nd material response primary washer

**Surface Treatment:**

Cadmium primary washer

**Surface Treatment Specification:**

G-4341-m code 15 fsc-16764 mfr ref 1st treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0