

View Online at <https://aerobasegroup.com/nsn/5305-01-086-9876>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.750 inches and 0.938 inches

**Fastener Length:**

Between 1.188 inches and 1.250 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.150 inches and 0.163 inches

**Width Between Flats:**

Between 0.428 inches and 0.438 inches

**Hole Diameter:**

Between 0.061 inches and 0.069 inches

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astm b633 type 2 sc 3 assn standard single treatment response

**Thread Series Designator:**

UNF

**Specification Or Standard:**

2 type and 10p style and 8 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0