NSN 5305-01-087-1145

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-087-1145 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.155 inches and 0.281 inches **Fastener Length:** Between 0.608 inches and 0.670 inches **Head Style:** Knurled no. 4 **Head Diameter:** 0.500 inches **Head Height:** Between 0.359 inches and 0.390 inches **First Diameter From Head:** Between 0.365 inches and 0.385 inches **Second Diameter From Head:** 0.164 inches **Third Diameter From Head:** 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.046 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.223 inches and 0.275 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.389 inches and 0.453 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Stainless steel **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-087-1145

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0