Externally Relieved Body Screw - Page 1 of 2

**AeroBase** Group

View Online at https://aerobasegroup.com/nsn/5305-01-087-1145
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.155 inches and 0.281 inches
Fastener Length:
Between 0.608 inches and 0.670 inches
Head Style:
Knurled no. 4
Head Diameter:
0.500 inches
Head Height:
Between 0.359 inches and 0.390 inches
First Diameter From Head:
Between 0.365 inches and 0.385 inches
Second Diameter From Head:
0.164 inches
Third Diameter From Head:
0.125 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.046 inches and 0.078 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 0.223 inches and 0.275 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
Between 0.389 inches and 0.453 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
3
Material:
Stainless steel
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0