## NSN 5305-01-087-1917

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-087-1917 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.378 inches and 1.500 inches **Fastener Length:** Between 1.440 inches and 1.500 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.312 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel **Screw Material Specification:** Qq-s-637 federal specification single material response or 66 federal standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response or mil-c-81562 type 2 cl 3 military specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 1 type and 10s style Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

No

A500d0

## NSN 5305-01-087-1917

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-81562 spec.