NSN 5305-01-087-1918



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-087-1918 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.391 inches **Fastener Length:** 1.766 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.704 inches and 0.762 inches **Hole Diameter:** Between 0.096 inches and 0.116 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.375 inches **Hole Quantity:** Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 4140 or steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Head Hole Configuration Style:** Round

N/a

Unf

Shelf Life:

Thread Series Designator:

NSN 5305-01-087-1918

Machine Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.