NSN 5305-01-087-3102

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-087-3102 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.750 inches **Head Style:** Thumb no. 4 **Head Height:** 0.880 inches Width Between Flats: 1.000 inches **Shoulder Length:** 1.000 inches **Point Length:** 0.032 inches **Shoulder Width Across Flats:** 0.390 inches First Diameter From Head: Between 0.208 inches and 0.212 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.511 inches and 0.531 inches Point Style: Flat **Thread Diameter:** 0.250 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Point Chamfer Angle:** 45.0 degrees **Shoulder Shape:** Square Material:

Steel

Material Specification:

Sc-a-706376-80063 mfr ref single material response

NSN 5305-01-087-3102

Thumbscrew - Page 2 of 2

Fiig: A003b0



Surface Treatment:
Enamel
Surface Treatment Specification:
Qq-p-416, type 2 mfr ref single treatment response
Test Data Document:
80063-sc-a-706141 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No