NSN 5305-01-087-3183

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-087-3183 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.156 inches **Fastener Length:** 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Stainless steel **Screw Material Specification:** 66 federal standard single material response **Head Surface Treatment: Passivate Shank Surface Treatment:** Oxide and passivate **Head Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Shank Surface Treatment Specification:** Mil-c-13924, class 4 military specification single treatment response and qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-087-3183

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.