NSN 5305-01-087-7012



Thumbscrew - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-087-7012 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 2.470 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.380 inches **Head Height:** 0.500 inches **First Diameter From Head:** Between 0.182 inches and 0.192 inches **Second Diameter From Head:** Between 0.135 inches and 0.145 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.720 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.220 inches **Point Style:** Flat **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303se or steel comp 303 **Material Specification:** Astm a582 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 ty1 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life: N/a

NSN 5305-01-087-7012

Thumbscrew - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0