Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-087-8774

| Thread Class: | |
|-----------------|---|
| 2a | |
| Thread Directi | on: |
| Right-hand | |
| Thread Length | |
| 0.281 inches | |
| Fastener Leng | th: |
| 0.812 inches | |
| Head Style: | |
| Knurled no. 1 | |
| Head Diameter | r: |
| 0.375 inches | |
| Head Height: | |
| 0.188 inches | |
| First Diameter | From Head: |
| 0.095 inches | |
| Distance From | Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.531 inches | |
| Internal Drive | Style: |
| Slot | |
| Thread Diamet | ter: |
| 0.138 inches | |
| Thready Qty P | er Inch (tpi): |
| 32 | |
| Externally Reli | eved Body Diameter Quantity: |
| 1 | |
| Material: | |
| Steel comp 303 | 3 |
| Material Speci | fication: |
| Qq-s-763 feder | al specification single material response |
| Surface Treatm | nent: |
| Passivate | |
| Surface Treatm | nent Specification: |
| Mil-f-14072 e30 | 00 military specification single treatment response |
| Thread Series | Designator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measu | re: |
| | |
| Demilitarizatio | n: |
| No | |

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-f-14072 spec.