NSN 5305-01-087-8776

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-087-8776 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.160 inches **Fastener Length:** 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.082 inches and 0.097 inches **First Diameter From Head:** 0.085 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.340 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Qq-s-763 300 series federal specification single material response or comp 16-18 or 18-8 assn standard single material response **Surface Treatment:** Passivate and chromate and enamel **Surface Treatment Specification:** Mil-f-14072 e300 military specification 1st treatment response and mil-p-8585 military specification 2nd treatment response and tt-e-527 color 36231 federal specification 3rd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-087-8776

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.