NSN 5305-01-087-9726

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-087-9726 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.057 inches and 0.062 inches **Fastener Length:** 0.127 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.1550 inches and 0.1555 inches **Head Height:** Between 0.122 inches and 0.127 inches **First Diameter From Head:** Between 0.0756 inches and 0.0759 inches **Second Diameter From Head:** Between 0.047 inches and 0.052 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.054 inches and 0.056 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.064 inches and 0.071 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.073 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-087-9726

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0