NSN 5305-01-088-2791

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-088-2791 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.303 inches and 0.313 inches **Fastener Length:** 1.750 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.495 inches and 0.505 inches **Head Height:** Between 0.546 inches and 0.578 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.239 inches and 1.249 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification 1st material response or astm a276 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-088-2791

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0