Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-088-2798



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.381 inches and 0.447 inches Fastener Length: Between 1.016 inches and 1.062 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.327 inches and 0.385 inches Locking Feature: Patch threads or pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4037 fastener or steel comp 8630 fastener **Material Specification:** Ams 6300 assn standard 1st material response fastener or mil-s-6050 military specification 2nd material response fastener Surface Treatment: Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response fastener **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

NSN 5305-01-088-2798

Socket Head Cap Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-s-6050 spec.