

View Online at <https://aerobasegroup.com/nsn/5305-01-088-5326>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.434 inches and 0.500 inches

Fastener Length:

Between 0.470 inches and 0.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.134 inches and 0.140 inches

Head Height:

Between 0.083 inches and 0.086 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.086 inches

Width Across Flats:

Between 0.0781 inches and 0.0791 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

Color:

Black

Material:

Steel

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl 1 military specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.