NSN 5305-01-088-7427

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-088-7427 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.000 inches and 1.120 inches **Fastener Length:** Between 6.500 inches and 6.620 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.530 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Material Specification:** 66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or astm a493 assn standard 6th material response **Surface Treatment: Passivate Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

6 type

Shelf Life:

N/a

NSN 5305-01-088-7427

Socket Head Cap Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0