NSN 5305-01-088-7955

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-088-7955

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.630 inches
Fastener Length:
1.000 inches
Head Style:
Knurled no. 4
Head Diameter:
0.500 inches
Head Height:
0.250 inches
First Diameter From Head:
0.380 inches
Second Diameter From Head:
0.280 inches
Third Diameter From Head:
0.380 inches
Fourth Diameter From Head:
Between 0.175 inches and 0.185 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.178 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter
0.240 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
0.303 inches
Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:
0.373 inches
Point Style:
Flat
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Externally Relieved Body Diameter Quantity:
4
Material:

Steel comp 303 or steel comp 303se

Material Specification:

Astm a582 assn standard all material responses

NSN 5305-01-088-7955

Thumbscrew - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 cl1 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: