NSN 5305-01-088-7955

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-088-7955

Thread	Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.630 inches

Fastener Length:

1.000 inches

Head Style:

Knurled no. 4

Head Diameter:

0.500 inches

Head Height:

0.250 inches

First Diameter From Head:

0.380 inches

Second Diameter From Head:

0.280 inches

Third Diameter From Head:

0.380 inches

Fourth Diameter From Head:

Between 0.175 inches and 0.185 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.178 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.240 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.303 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

0.373 inches

Point Style:

Flat

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Externally Relieved Body Diameter Quantity:

4

Material:

Steel comp 303 or steel comp 303se

Material Specification:

Astm a582 assn standard all material responses

NSN 5305-01-088-7955

Thumbscrew - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 cl1 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0