NSN 5305-01-089-2526

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-089-2526 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.413 inches and 0.479 inches **Fastener Length:** Between 0.610 inches and 0.656 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Locking Feature:** Pellet threads or strip threads or patch threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 fastener or steel comp 8630 fastener **Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-41 type 2 cl 3 federal specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-089-2526

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.