Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-089-2533

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.500 inches	
Fastener Length:	
Between 0.720 inches and 0.750 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.091 inches and 0.096 inches	
Head Height:	
Between 0.057 inches and 0.060 inches	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.060 inches	
Width Across Flats:	
Between 0.050 inches and 0.051 inches	
Thready Qty Per Inch (tpi):	
80	
Min. Tensile Strength (psi):	
80000 pounds per square inch	
Hardness Rating:	
80.0 rockwell b	
Minimum Yield Strength:	
30000 pounds per square inch	
Material:	
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316	
Material Specification:	
66 federal standard 1st material response or astm a582 assn standard 2nd material response	or 66 federal standard 3rd material response
or 66 federal standard 4th material response or 66 federal standard 5th material response	
Surface Treatment:	
Oxide	
Surface Treatment Specification:	
Mil-c-13924, cl 2 military specification single treatment response	
Thread Series Designator:	
Unf	
Specification Or Standard:	
6 type	
Shelf Life:	
N//	

N/a

NSN 5305-01-089-2533

Socket Head Cap Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.