

View Online at <https://aerobasegroup.com/nsn/5305-01-089-5697>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.250 inches and 0.380 inches

**Fastener Length:**

Between 0.350 inches and 0.380 inches

**Head Style:**

Watertight

**Head Diameter:**

0.493 inches

**Head Height:**

0.148 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Features Provided:**

O ring

**Thready Qty Per Inch (tpi):**

20

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Screw Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0