NSN 5305-01-089-5984

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-089-5984 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.246 inches **Fastener Length:** Between 0.516 inches and 0.561 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.287 inches and 0.334 inches **Head Height:** 0.042 inches **First Diameter From Head:** 0.138 inches **Second Diameter From Head:** 0.097 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.043 inches and 0.053 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.243 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** Furnished with tfe washer and o-ring Material: Steel comp 410

Surface Treatment:

Oxide

Material Specification:

Qq-s-763 federal specification single material response

NSN 5305-01-089-5984

Externally Relieved Body Screw - Page 2 of 2



Mil-c-13924 cl 2 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.