

View Online at <https://aerobasegroup.com/nsn/5305-01-089-5984>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.246 inches

Fastener Length:

Between 0.516 inches and 0.561 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.287 inches and 0.334 inches

Head Height:

0.042 inches

First Diameter From Head:

0.138 inches

Second Diameter From Head:

0.097 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.043 inches and 0.053 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.243 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

100.0 degrees

Externally Relieved Body Diameter Quantity:

2

Special Features:

Furnished with tfe washer and o-ring

Material:

Steel comp 410

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl 2 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.