

View Online at <https://aerobasegroup.com/nsn/5305-01-089-7667>

Thread Direction:

Right-hand

Thread Length:

6.75 millimeters

Fastener Length:

Between 14.7 millimeters and 15.0 millimeters

Head Style:

Fillister

Head Diameter:

15.0 millimeters

Head Height:

Between 3.35 millimeters and 3.65 millimeters

Hole Diameter:

1.30 millimeters

First Diameter From Head:

Between 7.2 millimeters and 7.6 millimeters

Second Diameter From Head:

10.0 millimeters

Third Diameter From Head:

Between 5.90 millimeters and 5.95 millimeters

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

3.55 millimeters

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

7.70 millimeters

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 14.7 millimeters and 15.0 millimeters

Internal Drive Style:

Slot

Thread Diameter:

10.0 millimeters

Hole Quantity:

1

Hole Type:

Drilled

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Thread Pitch In Millimeters:

1.5

External Thread Tolerance Class:

6g

Hole Configuration Style:

Round

Externally Relieved Body Diameter Quantity:

3

Material:

Steel

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Phosphate manganese and phosphate zinc

Surface Treatment Specification:

Mil-p-16232, type m military specification single treatment response or mil-p-16232, type z military specification single treatment response

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.