

View Online at <https://aerobasegroup.com/nsn/5305-01-089-7667>

**Thread Direction:**

Right-hand

**Thread Length:**

6.75 millimeters

**Fastener Length:**

Between 14.7 millimeters and 15.0 millimeters

**Head Style:**

Fillister

**Head Diameter:**

15.0 millimeters

**Head Height:**

Between 3.35 millimeters and 3.65 millimeters

**Hole Diameter:**

1.30 millimeters

**First Diameter From Head:**

Between 7.2 millimeters and 7.6 millimeters

**Second Diameter From Head:**

10.0 millimeters

**Third Diameter From Head:**

Between 5.90 millimeters and 5.95 millimeters

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

3.55 millimeters

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

7.70 millimeters

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 14.7 millimeters and 15.0 millimeters

**Internal Drive Style:**

Slot

**Thread Diameter:**

10.0 millimeters

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Thread Pitch In Millimeters:**

1.5

**External Thread Tolerance Class:**

6g

**Hole Configuration Style:**

Round

**Externally Relieved Body Diameter Quantity:**

3

**Material:**

Steel

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Phosphate manganese and phosphate zinc

**Surface Treatment Specification:**

Mil-p-16232, type m military specification single treatment response or mil-p-16232, type z military specification single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.