## NSN 5305-01-089-8679

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-089-8679 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.210 inches and 0.230 inches **Fastener Length:** Between 0.732 inches and 0.752 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.1670 inches and 0.180 inches **Head Height:** Between 0.033 inches and 0.049 inches **First Diameter From Head:** Between 0.076 inches and 0.079 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.502 inches and 0.542 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 4130 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-s-6758 spec.

Mil-std (military Standard):

A003b0