

View Online at <https://aerobasegroup.com/nsn/5305-01-090-1509>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.210 inches and 0.235 inches

Fastener Length:

Between 0.410 inches and 0.440 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.238 inches and 0.279 inches

First Diameter From Head:

0.138 inches

Second Diameter From Head:

Between 0.100 inches and 0.105 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.090 inches and 0.105 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.230 inches

Internal Drive Style:

Cross recess type 1

End Application:

An/alr-56c

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 100.0 degrees

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or stainless steel

Material Specification:

Comp 16-18 or 18-8 assn standard 6th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072 e300 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.