NSN 5305-01-090-4086

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-090-4086 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.202 inches and 0.222 inches **Fastener Length:** Between 0.985 inches and 1.015 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.235 inches and 0.250 inches **First Diameter From Head:** Between 0.080 inches and 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.685 inches and 0.705 inches **Point Style:** Cone **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 303 or steel comp 303se or steel comp 303ma or steel comp 303pb or steel comp 303 plus x or steel comp 304 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-090-4086 Thumbscrew - Page 2 of 2



Fiig:

A003b0