

View Online at <https://aerobasegroup.com/nsn/5305-01-090-7625>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.400 inches and 0.410 inches

Fastener Length:

0.690 inches

Head Style:

Hexagon countersunk

Head Height:

0.170 inches

Width Between Flats:

0.625 inches

Shoulder Diameter:

0.300 inches first shoulder and 0.305 inches first shoulder

Shoulder Length:

0.220 inches first shoulder and 0.230 inches first shoulder

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Countersink Angle:

15.000 degrees

Shoulder Shape:

Round first shoulder

Material:

Steel comp 1017 or steel comp 1029 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1115 or steel comp 1116 or steel comp 1117 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1030

Surface Treatment:

Zinc or cadmium

Surface Treatment Specification:

Qq-z-325 federal specification single treatment response or qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0