Socket Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-090-9072



| Thread Class: |
|--|
| 2a |
| Za Thread Direction: |
| |
| Right-hand |
| Thread Length: |
| Between 0.097 inches and 0.164 inches |
| Fastener Length: |
| Between 0.158 inches and 0.188 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.130 inches and 0.149 inches |
| Locking Feature: |
| Patch threads |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.073 inches |
| Thready Qty Per Inch (tpi): |
| 64 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 321 or steel comp 347 or steel comp 302 or steel comp 303 |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Specification Data: |
| 80205-nas662 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |
| No |
| Fiig: |
| A003b0 |