## NSN 5305-01-091-1192



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-091-1192 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.290 inches **Fastener Length:** 1.040 inches **Head Style:** Hexagon **Head Height:** 0.160 inches Width Between Flats: 0.375 inches First Diameter From Head: 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color lusterless green Material: Steel comp 202 or steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 420 or steel comp 430 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 446 **Material Specification:** Qq-s-763 cond a federal specification all material responses **Surface Treatment:** Paint grip **Surface Treatment Specification:** Mil-c-46168 military specification single treatment response head **Thread Series Designator:** 

**Unit Of Measure:** 

Shelf Life:

Unf

N/a

## NSN 5305-01-091-1192

Externally Relieved Body Screw - Page 2 of 2



|  |  |  | ati |  |
|--|--|--|-----|--|
|  |  |  |     |  |

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-46168 spec.