Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-091-1194

Thre	ad Class:
2a	
Thre	ad Direction:
Right	-hand
Thre	ad Length:
0.218	3 inches
Faste	ener Length:
0.593	3 inches
Head	I Style:
Flat o	chamfer
Head	I Diameter:
0.280) inches
Head	I Height:
0.120) inches
First	Diameter From Head:
0.086	b inches
Dista	nce From Largest Bearing Surface Of Head To End Of First Diameter:
0.375	5 inches
Inter	nal Drive Style:
Slot	
Thre	ad Diameter:
0.138	3 inches
Thre	ady Qty Per Inch (tpi):
32	
Exte	rnally Relieved Body Diameter Quantity:
1	
Mate	rial:
Steel	comp 303
Mate	rial Specification:
Astm	a582 assn standard single material response
Surfa	ace Treatment:
Oxide	9
Surfa	ace Treatment Specification:
Mil-c	13924 cl 2 military specification single treatment response
Thre	ad Series Designator:
Unc	
Shelf	f Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-c-13924 spec.