Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-091-1221

Thread Ciass. 3a Thread Direction: Right-hand Thread Length: 0.500 inches Fastener Length: 0.500 inches Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No Sti	Thread Class:
Thread Direction: Right-hand Thread Length: 0.500 inches Fastener Length: 0.500 inches Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit of Measure: Demilitarization: No	
Right-hand Right-hand Right-hand Thread Length: 0.500 inches Fastener Length: 0.500 inches Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Thread Length: 0.500 inches Fastener Length: 0.500 inches Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Head Jiameter: 0.138 inches and 0.138 inches Mith Across Flats: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
0.500 inchesFastener Length:0.500 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):190000 pounds per square inchHardness Rating:38.0 rockwell c170000 pounds per square inchMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:ToDemilitarization:NoFig:	-
Fastener Length:0.500 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):190000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:170000 pounds per square inchMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	-
0.500 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):190000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:170000 pounds per square inchMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	
Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-
Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Vidth Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Head Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):190000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:170000 pounds per square inchMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:	-
Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Head Height: Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Between 0.134 inches and 0.138 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: 35teel Steel Steel Steel Steel Steel Stefe Material: 1000 Sheff Life: N/a Unic Of Measure: Demilitarization: No	-
HexagonThread Diameter:0.138 inchesWidth Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):190000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:170000 pounds per square inchMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aInit Of Measure:Demilitarization:NoFig:	
Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Steel Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	-
Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
0.109 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: 170000 pounds per square inch Material: Steel Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
19000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Minimum Yield Strength: 170000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-
17000 pounds per square inch Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Material:SteelSurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	-
Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unc
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A003b0	Fiig:
	A003b0