## NSN 5305-01-091-3894

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-091-3894 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** 0.102 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.250 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Oxide and passivate **Surface Treatment Specification:** Mil-c-13924, class 4 military specification 1st treatment response and cqq-p-35 military specification 1st treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0

## NSN 5305-01-091-3894

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.