NSN 5305-01-092-6718

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-092-6718 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.135 inches and 0.145 inches **Fastener Length:** Between 0.510 inches and 0.525 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.221 inches and 0.231 inches **Head Height:** Between 0.057 inches and 0.062 inches **Internal Drive Style:** Cross recess type 1 **Material Accommodated Thickness:** Between 0.080 inches and 0.100 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 fastener **Material Specification:** Qq-w-423 cond b federal specification single material response spring **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig: A003b0

NSN 5305-01-092-6718

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-23195 spec.