

View Online at <https://aerobasegroup.com/nsn/5305-01-092-8693>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.875 inches

Fastener Length:

1.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.262 inches and 0.270 inches

Head Height:

Between 0.159 inches and 0.164 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.141 inches and 0.143 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Special Features:

Solid film lubricant applied to shank and threads iaw mil-I-8937 form b

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or stainless steel

Material Specification:

66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or com+16-18 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0