

View Online at <https://aerobasegroup.com/nsn/5305-01-092-9898>

Fastener Length:

Between 2.690 inches and 2.750 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.340 inches and 0.385 inches

Internal Drive Style:

Cross recess type 1

Min. Tensile Strength (psi):

55000 pounds per square inch

Nonmachine Thread Style:

Wood screw (type wd)

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Nonmachine Thread Diameter:

0.190 inches

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

Surface Treatment:

Cadmium and chromate or zinc and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl3 federal specification 1st treatment response or mil-c-81562 type 2 cl 3 military specification 1st treatment response or qq-z-325 type 2 cl 3 federal specification 2nd treatment response or mil-c-81562 type 2 cl 3 federal specification 2nd treatment response

Specification Or Standard:

1 type and 2c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.