## NSN 5305-01-092-9923

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-092-9923

Thread Class:
3a Thread Direction:
Right-hand
Thread Length:
Between 0.306 inches and 0.356 inches
Fastener Length: Between 0.441 inches and 0.471 inches
Head Style: Flat countersunk
Head Diameter:
Between 0.338 inches and 0.381 inches
Shoulder Diameter:
0.2177 inches first shoulder and 0.2182 inches first shoulder
Shoulder Length:
0.115 inches first shoulder and 0.135 inches first shoulder
Internal Drive Style:
High-torque Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32 Countercipt: Angles
Countersink Angle: Between 99.0 degrees and 101.0 degrees
Shoulder Shape: Round first shoulder
Special Features:
Internal hexagon socket in threaded end 0.079 in. Min and 0.086 in. Maximum width across flats
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-092-9923

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

