NSN 5305-01-093-0291

Close Tolerance Screw - Page 1 of 2

3a

32





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.250 inches and 0.300 inches Fastener Length: Between 0.635 inches and 0.665 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.270 inches and 0.302 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Grip Length: Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 8740 **Material Specification:** Mil-s-6049 military specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 type 1 cl 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure:

NSN 5305-01-093-0291

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.